

PRODUCT NO.	RoHS compliant
DSIC03THGER	

REV.	ECN NO.	DR	DATE

NOTES :

1.Specification:

- 1>.Operating force:1000gf Max
- 2>.Operating Temperature: -40° to+85°
- 3>.Storage Temperature: -40° to+85°
- 4>.Mechanical Life:3000cycles minimum
- 5>.Electrical Life:2000cycles 25mA 24VDC







2. PLATING:

GOLD FLASH 1u"~2u"SOLDERTAIL,
1u"~3u" GOLD PLATING ON THE CONTACT AREA,
WITH 50u" NICKEL UNDERPLATINGOVERALL.


3. PART NUMBER DESCRIPTION

DSIC XX T H G E R
 [包装方式: T=管装 R=Reel]
 [电镀层: E=接触部 1u"~3u" / 焊尾部 1u"~2u"]
 [G=镀金 S=内金外镀]
 [脚型: S脚 / J脚 / B脚 / A脚 / Z脚]
 [T=低推贴胶 S=低推不贴胶 L=长推]
 [产品数: 01=1P 03=3P 12=12P]

[Schematic]



RECOMMENDED P.C.B. LAYOUT (TOP VIEW)



Number	Part Name	Material	Finished	TOLERANCE UNLESS OTHERWISE SPECIFIED		INSPECTION	 东莞市广智实业有限公司 DongGuan Kingtek Industrial Co., Ltd.			
①	Actuator	UL94 V0	White	LINER	ANGLES	COPY				
②	Cover	UL94 V0	Black			PROJECTION				
③	Movable	Copper Alloy	1u"~3u"Gold	.00 ± 0.15	.0 ± 1°			TITLE BY DSIC SERIES PITCH 2.54mm		
④	Terminal	Brass	1u"~2u"Gold	.000± 0.10	.00± 0.5°	2012/04/12	PRODUCT FAMILY DSIC SERIES			
⑤	Base	UL94 V0	Black	DESIGN	kathy		PRAT NO. DSIC03THGER			
⑥	Terminal Contact	Brass	1u"~3u"Gold	DRAWING			FILE NO. DSIC03THGER-A			
⑦	Marly	UL94 V0	0.05mm	CHECK		SIZE	UNIT	SCALE	SHEET	REV.
				APPRO.		A4	mm	2 : 1	1 OF 1	A